



Commercial Order Desk:

P 613 244 3773

F 613 244 8553

E order@eurotilestone.com

General Inquiries:

P 613 244 4315

F 613 244 4320

E info@eurotilestone.com

3103 Hawthorne Rd | Ottawa, Ontario K1G 3V8

Connect with us on:



<http://eurotilestone.com/>

SONObase features

- Reduces transmission of impact and airborne noise in the floor system
- Superior level of sound absorption
- Stable dimensions
- Light and easy to cut
- Installation under a concrete screed is possible
- Made in Canada

LEED Information:

Materials and Resources -

MR 3, MR 4, MR 5, MR 6;

Indoor Environmental Quality -

IEQ 1, IEQ 2;

Innovation & Design Process -

IDP 1.

Scope: ALL TYPES OF FLOORING

Properties	Requirements	Nominal Value
Transverse load at rupture	ASTM C-209-10	5.44 kg 12 lb
Air Quality (CRI indoor quality program)	Category cc-10	Standard (cc - 902245)
Water absorption	ASTM C-209-14	5 % P / V max.
Linear expansion	ASTM D-1037-24	0.08 %
Compressive strength (10 % deformation)	ASTM C-165 (A)	131.68 kg / cm ² 45 lb / in ²
Thermal resistance	ASTM C-518	R = 1.45 RSI = 0.26

Physical Properties	Metric	Imperial
Density	352.40 kg / m ³	22 lb / ft ³
Panel size:	1.22 m x 2.44 m	48 in x 96 in
Area covered / panel:	2.97 m ²	32 ft ²
Thickness:	11 mm	7/16 in
Weight / panel	10 kg	22 lb
Number of panels / skid:	50 panels	

Ecological Properties

0 % - COV (g. / l.) - Volatile organic compounds

100% recycled and recyclable wood fibre

For additional information :
Customer support : 1 (800) 561-4279
Website : www.mslfibre.com

infoplus@mslfibre.com

Developed and
manufactured in
Canada

