




BIANCO ANTICO TERRACOTTA
GLOSSY WALL
2"X8"




BIANCO SETA TERRACOTTA
GLOSSY WALL
2"X8"



BIANCO VETRO TERRACOTTA
GLOSSY WALL
2"X8"



GRIGIO BASALTO TERRACOTTA
GLOSSY WALL
2"X8"



PEPE TERRACOTTA
GLOSSY WALL
2"X8"



VERDE LAGUNA TERRACOTTA
GLOSSY WALL
2"X8"



LINO TERRACOTTA
GLOSSY WALL
2"X8"



COTTO CERATO TERRACOTTA
MATTE WALL
2"X8"

*Terracotta tile with craquelé finish, must be sealed before grouting.
*Minimum 1/8" grout joint required.
*Must be cut dry, if using a wet saw, seal before cutting.

AVAILABLE FOR SPECIAL ORDER:













Special order products are subject to a minimum 8-12 week order time

COLOUR	FINISH	SIZES (IN) / SHAPE
		*Extended catalogue available upon request

Note from Manufacturer:

The surface of all the Craquelé tiles is crackled due to the glass contained in the glaze that is highly fusible and gives brightness and transparency to the colors. The surface of the tile crackles during the firing in the kiln, creating hairline superficial fissures. Coloring substances may be absorbed through these and stain the surface. It is recommended to cut the tiles dry (the tiles have to be sealed before wet cutting) as well as applying a penetrating sealer on the surface of the tiles before grouting.

TECHNICAL INFORMATION:

 Material:	Terracotta	 Water Absorption:	3-15 %
 Floor / Wall:	Wall	 Slip Resistance:	N/A
 Shade Variance:	V2	 Stain Resistance:	Resistance
 Breaking Strength:	N/A	 Frost Resistance:	Resistance
 Thickness:	9 mm	 Abrasion Resistance:	N/A
 Rectified Tile:	No	 Chemical Resistance:	Resistance

PACKAGING INFORMATION:

SIZE	2x8
U/M	Square Feet
UM / Box	5.59
UM / Pc	0.10
SF / Pallet	
Boxes / Pallet	